SCE 30 XSafe



31 kg Self-contained Ice Machine

Complete range: SCE 20 - SCE 30 - SCE 40 - SCE 50 - SCE 65 - SCE 90 - SCE 105

Technical features

- Stainless steel bodywork scotch brite
- Vertical pump
- Built-in cleaning system
- Easily accessible components
- Low power and water consumption
- Optimum ratio between ice production and bin capacity
- Reduced dimensions
- Double defrosting system
- XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.



Internal bin capacity



9 kg of ice

430 cubes

Type of ice

Full Cubes



Voltage

230/50/1 Standard version

115/60/1 - 220/60/1 Available on demand

Machine dimensions

Net size WxDxH 390 x 515 x 640 mm

Net weight 31 kg

Shipping size WxDxH 460 x 580 x 760 mm

Shipping weight 37 kg

chnology ap

fications



MILANO OFFICE Sales Dept. Tel. +39 02 93900215 e-mail: sales@simag.it Service Dept.

Tel. +39 02 93960357 e-mail: service@simag.it SIMAG FAR EAST Singapore Office Tel. ++65 6738 5393 e-mail: scotsman@scotsman.com.sg

www.simag.it


SCE 30


XSafe




31 kg Self-contained Ice Machine

Complete range: SCE 20 - SCE 30 - SCE 40 - SCE 50 - SCE 65 - SCE 90 - SCE 105







- 1. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 2. 3/16" WATER DRAIN
- 3. CORD SET
- 4. 3/4" GAS WATER INLET

DRAINAGE PER GRAVITY

Operating Limits

	Minimum	Maximum				
Air temperature	10°C	43°C				
Water temperature	5°C	38°C				
Water pressure	1 bar	5 bar				
Electrical voltage	-10 %	+10 %				

Specifications and design are subject to change without notice

Model	Voltage	Daily pro- duction kg	input	Refrigerant		Fuse	Consumptions (**)			
		10°C/10°C		Туре	Charge kg	A	kWh/ 100kg	kWh/ 24h	Water I/h	
SCE 30 A	230/50/1	31	430	R134a	0.270	10	n.a.	7	5.0	
SCE 30 W	230/50/1	28	350	R134a	0.240	10	63	14.5	33.0	
(4) 5										

^(*) Power Input: at 43°C Ambient Temperature

^(**) Water Consumption: at 32°C Air and 21°C Water